

Window decoration, advertising on smooth, even surfaces. Appliances/casings (e.g. white goods), surfaces in the POS segment



Self-Adhesive indoor

euromedia WonderTack Ghost uv

euromedia WonderTack Ghost uv is an innovative product solution! The highly transparent polyester film adheres to smooth, even surfaces without the use of an adhesive. This is made possible by "WonderTack" technology, which uses micro porous suckers. Totally sustainable and environmentally friendly, since the strong, bright UV coloured prints that it produces can be reused without any loss in adhesion and without leaving behind residues of adhesive. The back can even be wiped clean with a damp cloth if it gets dirty, and the product regains its full "adhesive" strength.

WonderTack Ghost uv has good dimensional stability and is particularly easy to apply without bubbles, even by inexperienced users. Processing in a cutter plotter is simple, thanks to the product's excellent dimensional stability and 45 mic. thick backing. If you prefer to print a white-based material, we would be pleased to provide you with information about our euromedia WonderTack.

Dimensions
170mic - 1270mm(50') - 20m

Product Code
70100109144



Hints & Tips

Wear our euromedia Allrounder Gloves when applying the finished graphics, to avoid fingerprints. Please note that WonderTack Ghost uv can be used on HP DesignJet L25500 and L26500. However, individual print tests have to be performed upfront.

euromedia WonderTack Ghost uv

Product Properties

Applications

- indoor
- application on flat surfaces

Properties

- PVC-Free
- removable adhesive
- transparent

Processing Tips

Clean the mounting object before applying. Adhesion may vary depending on the material and may be reduced under certain low-temperature conditions. Below -30°C adhesion to aluminium may be insufficient. Please carry out a suitable test before use.

To regain full adhesive strength, simply wash dirt and impurities off the back of the film.

Wear our euromedia Allrounder GLoves when applying the finished graphics, to avoid fingerprints.

Not recommendable to print light background patterns with low ink coverage, specially in gray color. Solid background patterns with less than 10% may show some pattern. Try to increase ink coverage. Please run a prior test before production.

Storage

The product should be stored in its original packaging at a room temperature of 15°C - 25°C and 40 - 60% relative humidity.



Specifications

Material	Polyethylene
Ink	UV, Latex
Thickness	170 mic
Liner	45 mic
Weight	225 g/m ²
Density	1,29 g/cm ³
Temperature resistency	-30°C to 60°C

Note

This information relates to the current state of our knowledge and is given without obligation to provide you with information about our products and their applications. The information we give does not absolve you from carrying out your own trials and tests of the suitability of our products for your intended application. We reserve the right to carry out modifications, which will result in an improvement to the product.

euromedia

FUJIFILM Deutschland

Niederlassung der FUJIFILM Europe GmbH
 Heesenstraße 31 40549 Düsseldorf DE
 Tel: +49 211-5089-326
 Fax: +49 211-5089-287
 grafische_systeme@fujifilm.de