

## euromedia Solvent WonderTack New

For repositionable advertising on smooth, even surfaces, appliances/covers (e.g. white goods), surfaces in the POS area

### Description

Highly innovative and environmentally friendly! The PVC-free polypropylene film adheres without adhesive to smooth, even surfaces. Thanks to its unique, micro-porous sucker technology Solvent WonderTack New can be applied and removed again quite simply as often as you like. No more unpleasant adhesive residues on the hands or surfaces.

New: WonderTack New is now even more impressive thanks to a particularly white satin matt surface that avoids glare and clearly promotes your advertising messages. The optimised strong backing allows ideal processing in cutter plotters.

### Application areas

- Indoor
- Advertising on smooth surfaces
- Appliances/covers (e.g. white goods)
- Surfaces in the POS area

### Properties

- Satin matt surface
- Reversible adhesion thanks to micro-porous sucker technology (without adhesive)
- Backing optimised for use in cutter plotters
- Environmentally friendly: PVC-free

### Processing tips

- Adhesion may vary depending on the material and may be reduced under certain low-temperature conditions. Below -30°C adhesion to aluminium may be insufficient. Please carry out a suitable test before use.
- To regain full adhesive strength, simply wash dirt and impurities off the back of the film.
- Wear our euromedia Allrounder Gloves when applying the finished graphics, to avoid fingerprints.

### Storage

The product should be stored in the original packaging at a room temperature of 10°C - 25°C and a relative humidity of approx. 50%.

### Note

This information relates to the current state of our knowledge and is given without obligation to provide you with information about our products and their applications. The information we give does not absolve you from carrying out your own trials and tests of the suitability of our products for your intended application. We reserve the right to carry out modifications, which will result in an improvement to the product.



### Specifications

Thickness	285 Mikron
Weight (gsm)	225 g/m <sup>2</sup>
Density	0,8 g/cm <sup>3</sup>
Opacity	95%
Whiteness	93%
Gloss	50%
Adhesion	-30°C to 60°C
Ink compatibility	Solvent, UV, Latex