## FUJ¦FILM



**Textiles** 

B1/M1 polyester textile for trade fairs, decorations, indoor and outdoor stage construction

## euromedia TexUs Textile 190 FR

High quality, light banner textile with top lie-flat properties for quality prints in solvent up to 3.1m wide! Graphics appear vibrant and high contrast on the matt white surface, which is totally non-reflective and therefore perfectly suited to applications in areas of extreme artificial lighting.

Unbeatably favourable price-performance ratio. Versatile in use, because TexUs Textile 190 FR is flame-retardant according to B1. Of particular interest, therefore, if you are producing for the European trade fair business. If you prefer to print a very bulky, heavy textile substrate but with the same printability and surface characteristics, we would be pleased to introduce you to TexUs Textile 280 FR!

#### Dimensions

190g - 1030mm(41`) - 50m, PSI 190g - 1370mm(54`) - 50m, PSI 190g - 2500mm(98`) - 50m, PSI 190g - 3100mm(122`) - 50m, PSI Product Code 70100098664 70100098617 70100098682 70100098781



#### **Hints & Tips**

In many applications you can save yourself the trouble of hemming: by simply cutting to size using the euromedia heat cutter. The material `welds itself` at the edges in the process. Simple, clean, without fraying

# FUJIFILM

### euromedia TexUs Textile 190 FR

### **Product Properties**

#### Applications

- indoor
- outdoor
- banners
- trade fairs

#### Properties

- OEKO-TEX
- PVC-Free
- fire classification B1
- backlit/translucent
- heat cutting
- cold cutting
- can be stitched

#### **Processing Tips**

We basically recommend that the print is left to dry out for 24 hours before finishing.

#### Storage

The product should be stored in its original packaging at a room temperature of  $15^{\circ}$ C -  $25^{\circ}$ C and 40 - 60% relative humidity.



#### Specifications

Material	Polyester
Ink	Solvent
Flame retardancy	B1
Gloss Level	Matt
Weight	190 g/m²

#### Note

This information relates to the current state of our knowledge and is given without obligation to provide you with information about our products and their applications. The information we give does not absolve you from carrying out your own trials and tests of the suitability of our products for your intended application. We reserve the right to carry out modifications, which will result in an improvement to the product.



#### FUJIFILM Deutschland

Niederlassung der FUJIFILM Europe GmbH Heesenstraße 31 40549 Düsseldorf DE Tel: +49 211-5089-326 Fax: +49 211-5089-287 grafische\_systeme@fujifilm.de