

euromedia BlockOut Vinyl

Description

euromedia BlockOut Vinyl is a double-sided white self-adhesive film for blocking out glass surfaces and printing with solvent and UV-curing inks. euromedia BlockOut Vinyl is totally opaque, thanks to its blockout layer.

Application areas

- Outdoor
- On smooth, even surfaces (especially glass)

Specifications

Thickness	180 microns
Adhesive	Polyacrylate adhesive
Adhesive weight	25 g/m ²
Application	Dry, damp
Adhesive strength	Immediately: ~ 3.8 N/25 mm After 1 week: ~ 7.5 N/25 mm
Light fastness	Light fastness rating 7-8 according to the blue wool scale
Temperature range	During application: From 15 °C Applied: -30 °C to +80 °C
Minimum durability	3 years' outdoor when applied vertically in a Central European climate

Application

The film may be applied dry or damp. Any whitening of the adhesive during damp application will disappear within a few days depending on the weather conditions.

The film may be easily removed from smooth surfaces even after longer periods of time.

Storage

The film may be stored before use for at least 3 years, calculated from the date of manufacture. This time period applies to storage under the correct conditions of 15-25 °C and a relative humidity of 50-60 %. In order to avoid potential pressure spots, we recommend that the film is stored vertically or suspended.

Please note:

This information relates to the current state of our knowledge and is given without obligation to provide you with information about our products and their applications. The information we give does not absolve you from carrying out your own trials and tests of the suitability of our products for your intended application. We reserve the right to carry out modifications, which will result in an improvement to the product. We are dealers in printing materials and do not manufacture them ourselves.