



High quality finishing and longlasting protection of indoor and up to 3 years outdoor graphics

Protective Films

euromedia Mono Laminate II gloss

euromedia Mono Laminate Ilis a cold laminate for the finishing and protection of indoor and outdoor graphics. The nice surface of the high clarity laminate produces a high quality finish and protects prints from damage.

The euromedia Mono Laminate series has a water-based adhesive, is available as matt and gloss version, and is made of a neutral-coloured, monomeric vinyl with a high degree of transparency and a UV filter. For across the board protection!

| Dimensions | Product Code |
|-----------------------------|--------------|
| 80mic - 1050mm(41,3') - 50m | 70100112984 |
| 80mic - 1372mm(54') - 50m | 70100112985 |
| 80mic - 1524mm(60') - 50m | 70100113287 |



Hints & Tips

Our basic recommendation is that you allow the print to dry out for 24 hours before finishing. If you re not able to lay out the complete strip, simply stand the prints on edge very loosely rolled up. Mesh boxes or drinks crates are perfect for placing underneath, as they allow the graphics to 'breathe'.

Issue date: 18.09.2015



euromedia Mono Laminate II gloss

Product Properties

Applications

- indoor
- outdoor

Properties

permanent adhesive

Processing Tips

We basically recommend that the print is left to dry out for 24 hours before finishing.

Storage

The product should be stored in its original packaging at a room temperature of 15°C - 25°C and 40 - 60% relative humidity.



Specifications

| Material | PVC, transparent |
|-------------------------|--------------------------------|
| Thickness | 80 mic |
| Liner | 0,062 mm thick; 72 g/m² weight |
| Adhesive type | Water-based acrylic |
| Tensile strength | > 160 % |
| Temperature resistency | -30 °C to +80 °C |
| Application temperature | Min. 10 °C |
| Outdoor durability | Up to 3 years |
| Shelf life | 2 years |

Note

This information relates to the current state of our knowledge and is given without obligation to provide you with information about our products and their applications. The information we give does not absolve you from carrying out your own trials and tests of the suitability of our products for your intended application. We reserve the right to carry out modifications, which will result in an improvement to the product.



FUJIFILM Deutschland

Niederlassung der FUJIFILM Europe GmbH Heesenstraße 31 40549 Düsseldorf DE Tel: +49 211-5089-326 Fax: +49 211-5089-287 grafische_systeme@fujifilm.de

Issue date: 18.09.2015