



High quality and stable polyester film with a fine silver back for indoor and short-term outdoor rollup systems. Suitable for solvent, latex and UV inks

Display Films

## euromedia RollUp Film Premium

euromedia RollUp Film Premium is manufactured from polyester with particularly high dimensional stability. This gives the 180 micron thick rollup film good stability in the display and excellent lie-flat properties. The matt white coating prevents annoying reflections from artificial lighting. The silver coating on the back gives 100% opacity and is the perfect finish for the extremely high quality appearance of this rollup film. Graphics on this media are rich in contrast with high strength colours.

A further plus for euromedia RollUp Film Premium: a special coating makes the material extremely robust and protects both the print and unprinted areas on the front and back from scratches. This is particularly important if a rollup is subjected to a high degree of mechanical stress and is frequently assembled and disassembled. Do you need a dimensionally stable rollup material for normal conditions and with low curl? If so, have a look at our RollUp Film Advanced. Are you looking for a display film for short-term applications and with a good price-performance ratio? If so, use euromedia RollUp Film Standard in the version for solvent, latex and UV inks or for water-based pigmented and dye-based inks.

### Dimensions

180mic - 0914mm(36") - 30m  
 180mic - 0914mm(36") - 50m  
 180mic - 1067mm(42") - 30m  
 180mic - 1067mm(42") - 50m  
 180mic - 1270mm(50") - 30m

### Product Code

70100109958  
 70100098311  
 70100109933  
 70100098317  
 70100109972



### Hints & Tips

Finish euromedia RollUp Film Premium for an even higher quality look and greatest mechanical protection by using Ultra HighProtection gloss, matt or crystal sand laminate. Roll up loosely with the print side facing outwards for transport. This will ensure that the whole graphics including the laminate remain intact

## euromedia RollUp Film Premium

### Product Properties

#### Applications

- indoor
- outdoor
- displays
- trade fairs

#### Properties

- PVC-Free
- Blockout

#### Processing Tips

We basically recommend that the print is left to dry out for 24 hours before finishing.

#### Storage

The product should be stored in its original packaging at a room temperature of 15°C - 25°C and 40 - 60% relative humidity.



#### Specifications

Material	Polyester
Ink	Solvent, Eco-Solvent, Latex, UV
Gloss Level	Satin matt
Back	Silver grey
Thickness	180 mic
Weight	240 g/m <sup>2</sup>
Surface	White

#### Note

This information relates to the current state of our knowledge and is given without obligation to provide you with information about our products and their applications. The information we give does not absolve you from carrying out your own trials and tests of the suitability of our products for your intended application. We reserve the right to carry out modifications, which will result in an improvement to the product.

**euromedia**

#### FUJIFILM Deutschland

Niederlassung der FUJIFILM Europe GmbH  
 Heesenstraße 31 40549 Düsseldorf DE  
 Tel: +49 211-5089-326  
 Fax: +49 211-5089-287  
 grafische\_systeme@fujifilm.de