

euromedia Street Vinyl

For short and medium-term applications on streets, pavements, car parks or tarmac areas

Description

The white gloss film has been designed for use in combination with euromedia Street Laminate on rough indoor and outdoor surfaces. Outdoor durability is up to 6 months, depending on mechanical wear. The self-adhesive sandwich repels snow and rain but is also removable.

Application areas

- For rough surfaces (e.g. streets, car parks, pavements), trade fairs, exhibitions, outdoor sporting events, promotional campaigns, festivals and opening events.
- Indoor and outdoor

Properties

- Excellent adhesion to rough indoor and outdoor surfaces
- Resistant to scratches and footprints
- Good non-slip properties
- Easy to remove (within 6 months)
- Good dimensional stability
- Optimum cost in use for short and medium-term application

Processing tips

- Street Vinyl must be used in combination with Street Laminate.
- Street Laminate must be applied flush with the edges to guarantee adhesion with the surface and avoid trip hazards.
- We recommend rounding off the corners of the graphics so that they have less area for attack.
- On rough surfaces the composite should be applied using a fan and damp cloth.
- The surface should have an application temperature of at least 10-15 degrees Centigrade and be dry and free of grease.
- Street Vinyl must not be applied to smooth, glazed and polished surfaces. (The adhesive strength will increase dramatically.)

Note

This information relates to the current state of our knowledge and is given without obligation to provide you with information about our products and their applications. The information we give does not absolve you from carrying out your own trials and tests of the suitability of our products for your intended application. We reserve the right to carry out modifications, which will result in an improvement to the product.



Specifications

Adhesive type	Polyacrylic adhesive (waterproof)
Adhesive weight	~ 100 g/m ²
Film thickness	80 mic
Surface	White glossy
Adhesive strength	~ 5 N/ 25 mm (immediately on concrete)
Temperature resistance	-30 °C to +70 °C
Ink compatibility	Solvent, UV, Latex
Shelf life	3 years after manufacture