

Universal banner material for medium-term indoor and outdoor applications



Outdoor Banner

## euromedia Frontlit Production FR

euromedia Frontlit Production FR is a robust 510 g banner material for volume solvent and UV jobs for medium-term indoor and outdoor use. The satin matt front side gives your advertising message an eye-catching and high-contrast appearance, which is reinforced by the low-glare surface. Because of its B1 certificate the product is also suitable for indoor use, for example, at trade fairs.

This universal banner offers clean eyeletting and is suitable for high frequency or heat welding. euromedia Frontlit Production is robust and tear-resistant. For advertising particularly high quality products and for long-term outdoor use we recommend euromedia Frontlit Plus FR. If it's just a short-term application, Project Banner White is the best product for the job.

### Dimensions

510g - 1100mm(43') - 25m
510g - 1370mm(54') - 25m
510g - 1600mm(63') - 25m
510g - 2100mm(83') - 50m
510g - 2500mm(98') - 50m
510g - 2640mm(104') - 50m
510g - 3200mm(126') - 50m
510g - 5000mm(197') - 50m

### Product Code

70100100306
70100100305
70100100307
70100100308
70100100309
70100100310
70100100311
70100109513



### Hints & Tips

euromedia Banner Bond helps to strengthen banner edges. Either double fold the banner at the edges before eyeletting or reinforce the eyelets (e.g. Banner Boost). Apply the eyelets 1-2 cm from the edge and with a spacing of 30-50 cm. Fit with semi-elastic straps for tensioning

## euromedia Frontlit Production FR

### Product Properties

#### Applications

- indoor
- outdoor
- displays
- banners

#### Properties

- fire classification B1
- can be eyelet
- can be welded
- tear-proof

#### Processing Tips

We basically recommend that the print is left to dry out for 24 hours before finishing.

#### Storage

The product should be stored in its original packaging at a room temperature of 15°C - 25°C and 40 - 60% relative humidity.



#### Specifications

Material	Polyester/ PVC coated
Ink	Solvent, Latex, UV
Flame retardancy	B1
Gloss Level	Satin matt
Weight	510 g/m <sup>2</sup>
Density	20x20 (DIN EN 1049-2)
Yarn	1000x1000 dtex (20x20 (DIN EN 1049-2))
Tensile strength	2200/2000 kg/mm <sup>2</sup>
Tearing Strength	300/250 N
Outdoor durability	Up to 2 years
Others	Denier: 1000

#### Note

This information relates to the current state of our knowledge and is given without obligation to provide you with information about our products and their applications. The information we give does not absolve you from carrying out your own trials and tests of the suitability of our products for your intended application. We reserve the right to carry out modifications, which will result in an improvement to the product.

**euromedia**

#### FUJIFILM Deutschland

Niederlassung der FUJIFILM Europe GmbH  
 Heesenstraße 31 40549 Düsseldorf DE  
 Tel: +49 211-5089-326  
 Fax: +49 211-5089-287  
 grafische\_systeme@fujifilm.de