



# DARKLITE™

## THE PHOSPHORESCENT HEAT TRANSFER FILM FOR A POWERFUL GREEN GLOW-IN-THE-DARK EFFECT

Looking for a glow-in-the-dark personalisation solution? Darklite is a soft touch and phosphorescent PU film that will provide a great green visual effect to all your creations in dark environments.

#### Special event costumes



How it looks in a standard environment



How it looks in dark environment

## **Product description**

- ✓ Great to reach a great green luminescent effect.
- ✓ Glows in dark environments after being exposed to the light.
- ✓ Charged by natural and artificial light.
- ✓ Very soft touch.
- ✓ White matte finish.



# Application key points

- ✓ Very easy to cut.
- ✓ Allows very small design to power up the glow in dark effect.
- $\checkmark$  Very easy to weed  $\rightarrow$  saves production time.
- ✓ Very strong adhesive backing that allows repositioning the design after weeding.

## Usage benefits

✓ Ideal for decorating special events costumes, or accessories that need to stand out in the dark.









**TECHNICAL DATA** 

### **SPECIFICATIONS**

Medium

Composition	Average Thickness	Carrier	Dimensions
Phosphorescent Polyurethane	130 µm	Adhesive & Transparent Polyester	50 cm x 10 m

# **APPLICATION INSTRUCTIONS**

Applies on	Cutting	Application Temp. & Duration
Cotton Polyester Acrylic Cotton/Polyester blends without repellent treatment	Use a Flex Blade 45°	150°C – 15 s 302°F – 15 s
Pressure	Peeling	

Cold

#### Step 1 – Cutting

Set up the cutting of your heat transfer film in mirror mode and use a standard flex blade of  $45^{\circ}$ .

#### Step 2 – Weeding

Remove the excess of material (easy weeding).

#### Step 3 – Application

Position your design on the textile and press it with a Sefa DUPLEX/ROTEX or equivalent at  $150^{\circ}C/302^{\circ}F$  for 15 seconds, with a medium pressure.

We do recommend the use of a silicone paper to protect the designs and the textile during the application.

#### Step 4 – Peeling

Peel the material while cold.

NOTE: We highly recommend you to perform tests before launching a production.

#### CARE AND MAINTENANCE RECOMMENDATIONS

Washing		Ironing	Tumble -dry	Dry cleaning
Up to 40°C/104°F		On reverse side only	Yes	Yes
Storage life	S	torage Tempe Lightnin	Position	
Up to 1	-	y room with	Away	Vertical

#### Care and maintenance:

✓ Always respect the garments' instructions.

- ✓ Wait 24 hours after the application before the first wash.
- $\checkmark$  Avoid the use of aggressive products.

#### Washing recommendations:

- ✓ Respect the textile recommendations.
- $\checkmark$  Preferably inside out to extend the design's life.
- $\checkmark$  Do not bleach.