FUJIFILM



Protection and finishing of 3D graphics, e.g. vehicle wraps

Protective Films

euromedia 3D Laminate gloss

Specially developed for demanding applications. The only wafer-thin (50 mic.) PVC film is easy to draw into crimps and over rivets.

The glossy surface not only gives the print crisp, brilliant colours, but acts at the same time as good protection against the effects of sunlight, humidity, dirt and chemicals. 3D Laminate gloss is a genuine cast PVC film with a durability of up to 7 years. As with all euromedia laminates, the special adhesive is protected by a tear-resistant liner.

Dimensions

50mic - 1370mm(54`) - 45,7m 50mic - 1520mm(60`) - 45,7m Product Code 70100098970 70100098671



Hints & Tips

Best combination: - euromedia 3D SmartApply - euromedia Soft/Strong Squeegee - euromedia Heat Gun - when laminating, always run the laminator at a temperature of 20-30°C

FUJIFILM

euromedia 3D Laminate gloss

Product Properties

Applications

- 3D wraps(full car wraps)
- outdoor

Properties

permanent adhesive

Processing Tips

We basically recommend that the print is left to dry out for 24 to 48 hours before finishing. Apply on clean and dry surfaces only.

Storage

The product should be stored in its original packaging at a room temperature of $15^{\circ}C - 25^{\circ}C$ and 40 - 60% relative humidity.

PERMANENT	OUTDOOR

Specifications

Material	PVC, transparent, cast
Gloss Level	Glossy
Thickness	50 mic
Tearing Strength	0,8 kg/cm
Tack	0,65 kg/cm
Release value	30 g/cm
Temperature resistency	-40°C - +79°C
Application temperature	4.4°C to 38°C
Outdoor durability	Up to 7 years
Others	Dimensional-stability: 0,25-0,5mm

Note

This information relates to the current state of our knowledge and is given without obligation to provide you with information about our products and their applications. The information we give does not absolve you from carrying out your own trials and tests of the suitability of our products for your intended application. We reserve the right to carry out modifications, which will result in an improvement to the product.



FUJIFILM Deutschland

Niederlassung der FUJIFILM Europe GmbH Heesenstraße 31 40549 Düsseldorf DE Tel: +49 211-5089-326 Fax: +49 211-5089-287 grafische_systeme@fujifilm.de