

CLAM SPORT RANGE



- Suitable for balls, caps, logos and shoes - Quick and tool-free change of elements

User friendly :

* Easy replacement of the plate * Automatic opening by electro-

- Optimal heat & pressure distribu-

- Robust frame

- Suitable for laser transfer applications, screen printing, sublimation on textile and textile transfer - Ideal for small productions

- Manufactured in France
- 2-year guarantee on the machine
- 10-year guarantee on heating

Set programs



QuickRelease® system


Fast heat up



Electromagnetic

OPTIONAL ACCESSORIES









Support table

CAP Accessory

BALL Accessory

SHOE Accessory

FLAT Plate



IMAS Grafica Srl Via Brisconno 10, Abbiategrasso (MI) +39 02.94.96.96.72 | servizioclienti@imasgrafica.com Web-site:www.imasgrafica.com

Pre-heat time

TECHNICAL CHARACTERISTICS

Type Operation Electromagnetic Clam

Platen sizeBall : Size 0 to 7 + Rugby
Cap : 17 x 8 cm (EU & US version)
Logo : 13 x 13 cm

Weight °C / °F Max Power Power supply Amperage 24 Kg 220 °C / 429 °F 600 W 240 V Single-phase 3 A

Applications Direct to Garment, Flex, Textile Sublimation, Laser Transfer, Screen Printing

Dimensions

899x503x231 mm 35x20x9 "

OPTIONAL ACCESSORIES



TAB-98 LITE Support table.



ACC-BALL Upper & lower ball accessory for Clam Sport.



ACC-CAP CB / US Upper & lower cap accessory for Clam Ball (European and US version available).



ACC-SHL-CB Lower logos & shoes accessory for Clam Sport.



PLA-6CB Flat heating plate for Clam Sport.





Electronics developed by Sefa Accurate and fast regulation (PID control) for a wide range of heat transfer products : Flex, flock, sublimation, screen printing transfer. Double timer (main + pre-heat) 2 cycle counters 3 settable programs Stop cycle function

From 0 to 570 sec (precision +/- 1%). From 0 to 220°C (precision +/- 1%).

Heating time to reach 180°C : 5 min.

QUICK SIZE CHANGE



DIMENSIONS



Box weight CAI-CLAMBALL : 15 kg

Non contractual document - Depending on changes in range, we reserve the right to modify the characteristics of our products.